

DESCRIPTION

The Vapor-Tight LED Linear Fixture offers the most rugged construction for the toughest conditions. Full gasketing and polycarbonate housings ensure protection against the elements. Ideal for commercial and industrial installations such as parking garages, elevator shafts, pool areas, and wash bays. Wet location rated and dimmable; includes a built-in emergency battery backup with 90-minute runtime minimum

ADDITIONAL INFORMATION

LED L70 LIFE: > 100,000 hours **UL NUMBER**: E524483 UL - 1598 **DLC PRODUCT ID: PLOMOT9P BI-LEVEL MOTION SENSOR**

Optional accessories: surface mounting kit included, chain and cable purchased

separately

SPECIFICATIONS

SKU PF-VAPOR-4/52/YDM/840/EM

FINISH LIGHT GRAY

OTHER FINISHES CUSTOM

COLLECTION VAPOR

POLYCARBONATE HOUSING MATERIAL

DIFFUSER POLYCARBONATE

PRIMARY LIGHTING

LIGHT SOURCE 52W LED

LUMENS 6812

#OF BULBS INTEGRATED **VOLTAGE** 120 - 277V

COLOR TEMP/CRI 4000K/CRI 80

DIMENSIONS

LENGTH	47.2"
HEIGHT	3.5"
HEIGHT	3.1"
BACKPLATE	N/A
WEIGHT	6.9 LBS

