



4"/6"/8" RECESSED LED DOWNLIGHTS











DESCRIPTION

Prottofos family of Recessed LED Downlights. Wattage and color temperature are both offered in 3 levels of adjustability. Also available with 8W emergency backup driver.

WATTAGE TABLE

MODEL	WATTAGE LEVELS	
4"	6/8/12 W	
6"	8/12/16 W	
6" HIGH-OUTPUT	20/26/33 W	
8"	12/16/22 W	

ORDERING INFORMATION

4" SKU: PF-CL-3436-12W-WH[-EM] 6" SKU: PF-CL-5943-16W-WH[-EM]

6" High-Output SKU:

PF-CL-5943-33W-WH[-EM] 8" SKU: PF-CL-8351-22W-WH[-EM]

(add the -EM suffix for batt backup)

SPECIFICATIONS

SKU	SEE ORDERING INFORMATION		
FINISH	WHITE		
OTHER FINISHES	CUSTOM		
MATERIAL	ALUMINUM		
EM RUNTIME	>90 MINUTES		
EM RECHARGE	24 HOURS		

PRIMARY LIGHTING

LIGHT SOURCE	SEE WATTAGE TABLE
EFFICACY	100LM/W
VOLTAGE	120 - 277V
COLOR TEMPS	3000K/3500K/4000K
CRI	80

DIMENSIONS

MODEL	4"	6"	8"
DIAMETER	3.38"	5.94"	8.27"
HEIGHT	3.63"	4.25"	5.12"
EXTENSION	N/A	N/A	N/A
WEIGHT	N/A	N/A	N/A

