

# CERTIFICATE OF COMPLIANCE

**Certificate Number** E524483  
**Report Reference** E524483-20210926  
**Issue Date** 2021-SEPTEMBER-29

**Issued to:** PROTTOFOS LLC  
1070 MARKA LANEALPHARETTAGAUSUS30004

**This certificate confirms that representative samples of** Light-emitting-diode Surface-mounted Luminaires  
See Addendum Page


Have been investigated by UL in accordance with the Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 1598-Luminaires  
**Additional Information:** See the UL Online Certifications Directory at <https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program  
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



# CERTIFICATE OF COMPLIANCE

**Certificate Number** E524483  
**Report Reference** E524483-20210926  
**Issue Date** 2021-SEPTEMBER-29

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.


LED Surface Mounted Luminaire:

PF-WRAP-4/YY/YDM/QQQ[a]

[a] - Where 'YY' can be any characters to represent power, 'QQQ' can be digitals, first 'Q' can be '7', '8' or '9' to represent Ra, like '7' means Ra=70, last 'QQ' can be any digitals to represent temperature color, like '30' means 3000K. There can be Y or N prior to DM in all of the model designations, Y represents dimmable, N represents Non-dimmable.

PF-NARROW-4/YY/YDM/QQQ[b], PF-NARROW-2/YY/YDM/QQQ[b], PF-VAPOR-4/YY/YDM/QQQ[b].

[b] - Where 'YY' can be any characters to represent power, 'QQQ' can be digitals, first 'Q' can be '7', '8' or '9' to represent Ra, like '7' means Ra>70, last 'QQ' can be any digitals to represent temperature color, like '30' means 3000K. There can be Y or N prior to DM in all of the model designations, Y represents dimmable, N represents Non-dimmable, the 4 FT and 8 FT models could provide with suffix (EM) which represents emergency driver provided.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

