Certificate Number:

[E524483]

Report Reference:

E524483-20241214

Issue Date:

2024-December-14

Issued to:

PROTTOFOS LLC 1070 MARKA LANE ALPHARETTA, GA 30004 United States

This certificate confirms that representative samples of:

Light-emitting-diode Surface-mounted Luminaires

See Addendum Page

Has been evaluated by UL LLC in accordance with Standard(s) for Safety:

[UL 1598Luminaires]

Additional Information:

See UL Product iQ[®] at https://iq.ulprospector.com for additional information.

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.

David Piecuch

UL Mark Certification Program Owner



Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact UL Solutions Customer Service at https://www.ul.com/contact-us.

Certificate Number: E524483

Report Reference: E524483-20241214 **Issue Date:** 2024-December-14

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.]

LED Surface Mounted Luminaire:

PF-SL-WP149-40W-%-abcde (b), PF-SL-WP149-60W-%-abcde (b), PF-SL-WP149-80W-%-abc (b), PF-SL-WP149-100W-%-abc (b), PF-SL-WP149-120W-%-abc (b), PF-SL-WP149-150W-%-abc (b)

(b) PF=Company name, SL=Category name, WP149=Product name"_, __W" indicates the full wattage of the fixture;"%" can be any two letters for housing color;"a" can be "PH" or blank for photosensor provided or not;"b" can be "MS" or blank for motion sensor provided or not;"c" can be "SP" or blank for surge protector provided or not; "d" can be "EM" or blank for emergency driver provided or not; "e" can be "AU" or blank for auxiliary driver provided or not.

LED Surface Mounted Luminaire:

PF-SL-AL180-70W-%-%-abcd (d), PF-SL-AL180-100W-%-%-abcd (d), PF-SL-AL180-150W-%-%-abcd (d), PF-SL-AL180-200W-%-%-abcd (d), PF-SL-AL180-240W-%-%-abcd (d), PF-SL-AL180-375W-%-abcd (d)

(d) PF=Company name, SL=Category name, AL180=Product name, "___W" indicates the full wattage of the fixture; "%" can be any two letters for housing color; -% can be blank for T3 lens, can be any other letters for different diffuser light angle type; "a" can be "PH" or blank for photosensor provided or not; "b" can be "MS" or blank for motion sensor provided or not; "c" can be "SP" or blank for surge protector provided or not; "d" can be "AM", "YM", "AD", or "FM" for bracket type, or blank for DM1 pole bracket.

LED Surface Mounted Luminaire: PF-EM-710-15W-%-a (f)

(f) PF=Company name, WP710=Product name, "___W" indicates the full wattage of the fixture; "%" can be any two letters for housing color. "a" can be "PH" or blank for photosensor provided or not.



Certificate Number: E524483

Report Reference: E524483-20241214 **Issue Date:** 2024-December-14

LED Surface Mounted Luminaire:

PF-SL-WP736-15W-%-abcde (h), PF-SL-WP736-30W-%-abcde (h), PF-SL-WP736-50W-%-abcde (h), PF-SL-WP736-80W-%-abcde (h)

(h) PF=Company name, SL=Category name, WP736=Product name, "___W" indicates the maximum wattage of the fixture; "%" can be any two letters for housing color; "a" can be "PH" or blank for photosensor provided or not; "b" can be "MS" or blank for motion sensor provided or not; "c" can be "SP" or blank for surge protector provided or not; "e" can be "AU" or blank for auxiliary driver provided or not.

LED Surface Mounted Luminaire:

PF-LF-2433-25W-WH-abcd (j), PF-LF-4833-40W-WH-abcd (j), PF-LF-9633-70W-WH-abcd (j)

(j) PF=Company name, LF=Category name "####"=Product name derived from dimensions, "__W" indicates the maximum wattage of the fixture; "WH" indicates a white housing color; "a" can be "MS" or blank for motion sensor provided or not; "b" can be "EM" or blank for emergency driver provided or not; "c" can be "WG" or blank for wire guard provided or not. "d" can be "S" or blank for quick connector provided or not.

LED Surface Mounted Luminaire:

PF-SL-FL423-15W-%-abc (I), PF-SL-FL423-30W-%-bc (I), PF-SL-FL423-50W-%-bc (I), PF-SL-FL423-80W-%-bc (I)

(I) PF=Company name, SL=Category name, FL423=Product name, "___W" indicates the maximum wattage of the fixture; "%" can be any two letters for housing color; "a" can be any two digits for CCT; "b" can be "SP" or blank for surge protector provided or not; "c" can be "AM", "FM", or "YM" for bracket type provided.



Certificate Number: E524483

Report Reference: E524483-20241214 **Issue Date:** 2024-December-14

LED Surface Mounted Luminaire:

PF-SL-CP104-25W-%-ab (n), PF-SL-CP104-40W-%-ab (n), PF-SL-CP104-55W-%-ab (n), PF-SL-CP104-75W-%-ab (n), PF-SL-CP104-100W-%-ab (n)

(n) PF=Company name, SL=Category name, CP104=Product name, "___W" indicates the maximum wattage of the fixture; "%" can be any two letters for housing color; "a" can be "MS" or blank for motion sensor provided or not; "b" can be "SP" or blank for surge protector provided or not.

LED Surface Mounted Luminaire:

PF-SL-PT126-75W-%-%-acd (q), PF-SL-PT126-100W-%-%-acd (q)

(q) PF=Company name, SL=Category name, PT126=Product name, "___W" indicates the maximum wattage of the fixture;. "%" can be any two letters for housing color; -% can be blank for T3 lens, can be any other letters for different diffuser light angle type; "a" can be "PH" or blank for photosensor provided or not; "c" can be "SP" or blank for surge protector provided or not; "d" can be "AM", "DM", "AD", or "GM" for bracket type provided.

LED Surface Mounted Luminaire: PF-SL-UL33-25W-%-a (s)

(s) "%" can be any two letters for housing color, BZ for bronze; "a" can be "PC" or blank for photosensor provided or not.

